

P3 GRP Tubing Specifications 2.875" & 3.500"



P3 GRP Pipe Specifications

Specifications	2.7/8" 2000psi	3.1/2" 2000psi
Inside Diameter	2.37"/60.2mm	2.94"/74.7mm
Outside Diameter	2.78"/70.6mm	3.44"/87.4mm
Weight/Length	1.60lbs/ft-2.4kg/m	2.3 lbs/ft-3.4kg/m
Connection Diameter	4.00"/101.6mm	4.80"/121.9mm
Pin Up-Set Diameter	3.10"/78.7mm	3.75"/95.3mm
Connection Make-Up Loss Length	2.88"/7 mm	3.13"/79.4mm
Internal Pressure Rating	2000psi/138bar	2000psi/138bar
Collapse Pressure Rating	2400psi/165bar*	2300psi/159bar*
Average Tensile Rating	17,500lbs/8,000kg	24,000lbs/11,000kg
Temperature Rating	200F/93.3 C	200F/93.3C
Density	122lbs/cu.ft.-196kg/ltr	122lbs/cu.ft.-196kg/ltr
Thread Form to API 5B Table 14, 14 th Edition	2.7/8" EUE 8rd	3.1/2" EUE 8rd
Thread Make-Up Torque Opt/Min/Max (ft/lbs)	185/150/250**	225/175/300**

*100% of joints factory pressure tested to 1.25x Pressure Rating

**Make-Up using No.5 Strap Tool recommended